

ABS SCHEDULE 40 SOLID WALL DWV PIPE

Size	Length	Item #	Average O.D.	Min. Wall Thickness	Pieces Per Lift	Feet Per Lift
1-1/2"	10'	ASW-11210	1.905	0.145	259	2,590
	12'	ASW-11212	1.905	0.145	259	3,108
	20'	ASW-11220	1.905	0.145	259	5,180
2"	10'	ASW-20010	2.380	0.154	167	1,670
	12'	ASW-20012	2.380	0.154	167	2,004
	20'	ASW-20020	2.380	0.154	167	3,340
3"	10'	ASW-30010	3.507	0.216	75	750
	12'	ASW-30012	3.507	0.216	75	900
	20'	ASW-30020	3.507	0.216	75	1,500
4"	10'	ASW-40010	4.507	0.237	48	480
	12'	ASW-40012	4.507	0.237	48	576
	20'	ASW-40020	4.507	0.237	48	480
6"	10'	ASW-60010	6.625	0.280	24	240
	12'	ASW-60012	6.625	0.280	24	288
	20'	ASW-60020	6.625	0.280	24	480

SPECIFICATIONS:

Product Standards	ASTM D2661, CSA B181.1, NSF/ANSI 14
Material Standard	ASTM D3965, Cell Class 4-2-2-2
Pressure Rating	For Non-Pressure Use Only
Temperature Rating	-40° F to 140° F
End Finish	Plain End
Listings	IAPMO File 1909

